

UNITED NATIONS SUPPLY DEPOT
 Military Airport
 P.O. Box 323
 Pisa, Italy

COMMUNICATIONS SECTION

Receiver Final Test Sheet

Manufacturer: *Stewart-Warner Elec.*
 Model: *R-392/URR*
 Serial Number: *1315*

Date: *5 Juni 1966*
 Tested by: *Vanderaald*

Remarks:

I If response:

Band width Selector at *2* Khz. (Narrowest setting)
 Band width at 3 db down: *2*... Khz.
 Band width at 6 db down: *3*... Khz.

Band width Selector at *8*...Khz. (Widest setting)
 Band width at 3 db down: *10,4* Khz.
 Band width at 6 db down: *12,4* Khz.

III Sensitivity: signal + noise: noise ratio 10:1.

Mhz	microvolts	Mhz	microvolts	Mhz	microvolts	Mhz	microvolts
0,5	<i>5</i>	1,99	<i>1,1</i>	6	<i>4,5</i>	16	<i>4</i>
0,75	<i>6,3</i>	2	<i>4,5</i>	7,99	<i>4</i>	24	
0,99	<i>1,2</i>	3	<i>3,1</i>	8	<i>4</i>	31,99	
1	<i>1</i>	3,99	<i>1,1</i>	12	<i>5</i>		
1,5	<i>1,1</i>	4	<i>5,5</i>	15,99	<i>2,8</i>		

Audio response, reference 0dbm at 1000 hz:

Hz 100 200 300 500 1k 3k 5k 7k
 dbm *-1* *0* *-5*

Calibration Oscillator test

OK.

BFO Test

OK.